

Low-Voltage Residential Battery

IP21 Lithium Battery:
BLF-B51100 (5.12kWh)
BLF-B51150 (7.68kWh)

The BLF-B51100 Lithium battery system is ideal for new installation of household energy storage. With high energy density and wall-mounted solution, BLF-B51100 battery system is space-saving for indoor installation. To serve increasing load requirement, the flexible expansion can fit your energy demand of today and tomorrow.

Product Benefits

- ✔ Intelligent BMS with multiple protections
- ✔ IP21 supporting indoor installation
- ✔ Reliable performance: high efficiency and 90% DOD
- ✔ Double and robust mechanical protection
- ✔ Long cycle life and safest prismatic LFP batteries
- ✔ Easy and quick installation and expansion with modular design, up to 5 units in parallel



Low-Voltage Residential Battery

BLF-B51100/B51150

Model	BLF-B51100	BLF-B51150
Cell Type	LFP	
Nominal Voltage	51.2V	
Operating Voltage Range	43.2V - 57.6V	
Nominal Capacity	100Ah	150Ah
Nominal Energy	5.12kWh	7.68kWh
Max. Power	Charge: 4.1kw; Discharge: 5.12kw	Charge: 5.12kW; Discharge: 5.12kW
Depth of Discharge	100%, recommending 90%	100%, recommending 90%
Usable Energy	5.12kWh	7.68kWh
Dimension(W*H*D)	335*622*135.5 mm	364*585*165.5 mm
Weight	42.6kg	63kg
Max. Charge/Discharge Current	100A / 100A	
Operating Temperature	Charge: 0°C - 50°C; Discharge: -20°C - 55°C	
Operating Humidity	5% - 95%	
Storage Temperature	-20°C to +60°C	
Operating Attitude	< 4000m	
Communication	RS485 / CAN	
Scalability	Up to 5 Modules / 25kWh	Up to 5 Modules / 38.4kWh
Cooling Type	Natural	
Ingress Protection	IP21	
Installation Location	Wall-mounted	
Cycle Life	6000 Cycles[1]	
Authentication Level	IEC61000/UN38.3	

[1]: Test conditions: 0.5C Charge/0.5C Discharge, @25°C, 90% DOD, 70% EOL